$IA\text{-}2104\text{-}U\stackrel{\text{USB}}{\overset{\text{4 Relays}}{\overset{\text{Relays}}{\overset{\text{Controlled Module}}{\overset{\text{Module}}{\overset{\text{Nodel}}}{\overset{\text{Nodel}}{\overset{\text{Nodel}}{\overset{\text{Nodel}}{\overset{\text{Nodel}}{\overset{\text{Nodel}}{\overset{\text{Nodel}}}{\overset{\text{Nodel}}{\overset{\text{Nodel}}}{\overset{\text{Nodel}}{\overset{\text{Nodel}}{\overset{\text{Nodel}}{\overset{\text{Nodel}}}{\overset{\text{Nodel}}{\overset{\text{Nodel}}{\overset{\text{Nodel}}{\overset{\text{Nodel}}{\overset{\text{Nodel}}}{\overset{\text{Nodel}}}{\overset{\text{Nodel}}}{\overset{\text{Nodel}}}{\overset{\text{Nodel}}}{\overset{\text{Nodel}}}{\overset{\text{Nodel}}}{\overset{\text{Nodel}}}{\overset{\text{Nodel}}}}{\overset{\text{Nodel}}}{\overset{\text{Nodel}}}{\overset{\text{Nodel}}}{\overset{\text{Nodel}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}$





Features

- 4 SPDT USB Relays
- USB Powered & Controlled
- Easy Operation
- IA-3000 Series Compatible
- Software Drivers & Samples
- Small Footprint
- DIN Rail Mounted

Introduction

The IA-2104-U is a USB Relay controller module, powered and controlled by a USB port.

The IA-2104-U includes 4 SPDT Power Relays, with contact rating of 8 amp both at 30VDC and 240VAC.

The IA-2104-U is software compatible to the Intelligent Appliance IA-3000 Series.

Specifications

Control Port

Communication Method:

USB

Default BR:

19200, 8, n, 1

Relay OUTPUT

Relay Type: Contact Rating: SPDT Form C 8A @ 240 VAC

8A @ 30 VDC

Relay ON Time: Relay OFF Time: Channels: 5 ms 5 ms

General

Supply Voltage: USB Powered Dimensions: 0-60°C 110x45x20 Dimensions for DIN RAIL: 114x56x40

Weight: 125 gr

Ordering Information:

■ IA-2104-U - 4 Relays, USB Controlled Module and USB cable.